



A Review of Study of Ambient Air Quality Monitoring in Bhopal City

Mohit Singh Parmar¹, Prof. R. K. Bhatiya²

¹Research scholar, ME (Environmental Engineering) Jabalpur Engineering College, Jabalpur (M.P) 482011, India

²Associate Professor, Department of Civil Engineering, Jabalpur Engineering College, Jabalpur (M.P) 482011, India

ABSTRACT

Ambient air quality refers to the quality of outdoor air that surrounds us in environment. It is influenced by variety of factors, including natural sources such as dust and pollen, as well as anthropogenic sources such as transportation and industry. Outdoor air pollution causes public health hazards like cardiovascular disease, respiratory diseases etc. Assessment is necessary to be carried out in urban areas which are severely exposed to outdoor air pollution. Air pollution is mainly associated with industrial and automobile sources of which motor vehicles are of major concern. TO carry out study on assessment of ambient air quality parameters like Sulphur Dioxide (SO₂), Oxides of Nitrogen as NO₂, Respirable Suspended Particulate Matter (RSPM / PM₁₀) and Fine Particulate Matter (PM_{2.5}) various methods can be adopted to monitor air quality. This study will lead us to discuss various approaches and methods to assess ambient air quality and counter air pollution.

Keywords : Ambient Air , Air Pollution, Monitoring,

1. INTRODUCTION

The air pollution refers to the presence of harmful substances and particles in the air we breathe. These pollutants can come from a variety of sources, including factories, vehicles, power plants, and natural sources like wildfires and dust storms. The most common air pollutants include particulate matter, nitrogen oxides, sulphur dioxide, ozone, and carbon monoxide. Air pollution can have serious consequences for human health, including respiratory problems like asthma and bronchitis, increased risk of heart disease and stroke, and even cancer. It can also harm the environment, damaging crops and forests and contributing to climate change. The urban air quality is very important and enhanced the life of living beings. The recent studies in various places of the world revealed an increase in levels of ozone (O₃) and particulate matter (PM).

Central Pollution Control Board is executing a nation-wide programme of ambient air quality monitoring known as National Air Quality Monitoring Programme (NAMP). The network consists of 804 operating stations covering 344 cities/towns in 28 states and 6 Union Territories of the country. Under N.A.M.P., four air pollutants viz., Sulphur Dioxide (SO₂), Oxides of Nitrogen as NO₂, Respirable Suspended Particulate Matter (RSPM / PM₁₀) and Fine Particulate Matter (PM_{2.5}) have been identified for regular monitoring at all the locations. to high levels of air pollution can cause a variety of adverse health outcomes. It increases the risk of respiratory infections, heart disease, stroke and lung cancer. Both short and long-term exposure to air pollutants have been associated with health impacts. More severe impacts affect people who are already ill. Children, the elderly and poor people are more susceptible. Although air quality in high-income countries has been generally improved over the last decades, the adverse health effects of particulate air pollution, even at relatively low levels, remain a global public health concern. Air pollution very often has multiple sources and acting on a single one may not bring enough benefits for health. Although most newer motor vehicles have more efficient engines and are using cleaner fuels, the absolute number of vehicles is still increasing in many cities worldwide -- and consequently so are levels of ambient air pollution. Indeed, in parts of Europe where stricter standards and regulations for vehicles have been enforced, ambient air pollution levels are stable or decreasing, yet air quality levels are still above the WHO AQG values. Air pollution is a matter of major concern in India. In recent years the world has seen the changes in climatic conditions and these changes have been significantly contributed to change in air quality in such manner that has been created a lot of circumstances causing inconvenience and diseases to human beings. Such type of challenges not only causing health hazards but also it causes more expenditure done by government to combat air pollution. The ministry of environment, forests and climate change has been allocated Rs 3,079 crore for financial year 2024 which is a 24% increase over the revised estimates of financial year 2023. The developing nations like India is facing increased air pollution because of ongoing urbanization. In Indian cities pollutants are either emitted from natural sources or anthropogenic sources. Under National Air Quality Monitoring Programme (NAMP) which is executed by CPCB across the India, it has been suggested to focus mainly on four pollutants viz., Sulphur Dioxide (SO₂), Oxides of Nitrogen as NO₂, Respirable Suspended Particulate Matter (RSPM / PM₁₀) and Fine Particulate Matter (PM_{2.5}).

2. Air Pollution in Bhopal:

Geographically, Bhopal has an average elevation of 500 metres (1401 ft) and is located in the central part of India, just north of the upper limit of the Vindhya mountain ranges. Located on the Malwa plateau, it is higher than the north Indian plains and the land rises towards the Vindhya Range to the south. The city has uneven elevation and has small hills within its boundaries. The prominent hills in Bhopal are the Idgah and Shyamala hills in the northern region, together with the Katara hills in the southern region. There are 17 lakes and 5 reservoirs biggest of them are upper lake and lower lake. The Upper Lake has a surface area of 36 km² and catchment area of 361 km² while the Lower Lake has a surface area of 1.29 km² and catchment area of 9.6 km². Recently, Bhopal Municipal Corporation came with a resolution to involve local citizens in cleaning, conserving and maintaining the lakes. Bhopal city is divided into two parts where one part which is near the VIP and lake is Old Bhopal (north) and the other, New Bhopal (south), where malls are mainly situated. Major air pollutant present in the city are; PM_{2.5}, PM₁₀, SO₂, NO₂, NH₃, O₃, CO, Ni & As. As per the data of CPCB, following tables present monitoring results and trends from 2016-2020 .

TABLE- 1 Annual Average value of PM 10($\mu\text{g}/\text{m}^3$)

STATION	YEAR				
	2018	2019	2020	2021	2022
	PM ₁₀	PM ₁₀	PM ₁₀	PM ₁₀	PM ₁₀
Barkatulla University, Hoshgabad Road, Bhopal	111	117	126	131	107
Kolar Thana, Kolar Road, Bhopal	134	124	150	141	147
Nutan Subhash School, T.T. Nagar	90	76	67	77	83

TABLE – 2 Annual Average value of PM 2.5($\mu\text{g}/\text{m}^3$)

STATION	YEAR				
	2018	2019	2020	2021	2022
	PM _{2.5}	PM _{2.5}	PM _{2.5}	PM _{2.5}	PM _{2.5}
Barkatulla University, Hoshgabad Road, Bhopal	53	61	68	55	66
Kolar Thana, Kolar Road, Bhopal	60	71	78	82	71
Nutan Subhash School, T.T. Nagar	40	45	48	51	43

3. Air Quality Monitoring

The methods of measurement prescribed by CPCB for respective parameters are the combination of physical method, wet-chemical method and continuous online method. The continuous online ambient air quality monitoring systems are equipped with analyzers for measurement of PM₁₀, PM_{2.5}, SO₂, CO, NO₂, O₃, NH₃ and Benzene. The metallic parameters Pb, Ni, As are measured offline using filter based air samplers. The ambient air quality monitoring station (AQMS) consists of following systems:

- PM₁₀ & PM_{2.5}: Operates on the principle of Beta Ray Attenuation and measures Particle Mass concentration ranging from 0 to 5 mg/m³ with Minimum detection limit 1 $\mu\text{g}/\text{m}^3$. The equipment includes a PM₁₀ inlet and PM_{2.5} inlet.
- NO_x and NH₃: Operates on the principle of Chemiluminescence method, ranging from 0 to 2000 $\mu\text{g}/\text{m}^3$ with minimum detection limit 0.5 $\mu\text{g}/\text{m}^3$.
- SO₂ Analyser: Operates on the principle of UV Fluorescence method, ranging from 0 to 2000 $\mu\text{g}/\text{m}^3$ with minimum detection limit 0.5 $\mu\text{g}/\text{m}^3$.
- O₃ Analyser: Operates on the principle of UV Photometry method, range : 0 to 2500 $\mu\text{g}/\text{m}^3$ with minimum detection limit 0.5 $\mu\text{g}/\text{m}^3$.
- Multigas Calibrator: to calibrate gas analyzers manually, remotely controlled or automatically, for quality assurance. Multi Calibration upto 20 points.
- Automatic Weather Station (AWS): Ultrasonic Wind Sensor, Barometric Pressure, Temperature, Relative Humidity, Rainfall, Solar Radiation etc.

All these instruments except AWS are housed in a room or walk-way shelter with proper sampling system for gaseous and particulate matter parameters. AQMS should have the calibration facility for onsite calibration with zero and standard gases. Beta Ray Attenuation for the measurement of PM₁₀ and PM_{2.5} should be calibrated with standard filters. The detailed guideline for site selection, measurement frequency, reporting etc has been notified by CPCB. Each AQMS should also have a PC for recording and transmission of the data via internet.

4. Air Quality Monitoring Mechanisms

A. Air Quality Monitoring System (AQMS): This system consists the Air Quality Walkway Shelters with different air quality analyzers, Calibration System, Zero Air Generator, Sampling System, UPS, ACs and control computer installed in the Shelter. The main control room computer receives data from all AQMS control computers in a particular city, Central Control Room Server at IITM, Pune and FTP server at each stations control room.

B. Digital Display System (DDS): It consists of LED and LCD digital display boards along with a control computer to receive data from FTP server and to transmit the same to display boards.

C. Automatic Weather Stations (AWS): AWSs have been installed in some cities adjacent to Air Quality Walkway Shelters with a computer in control room of respective city to receive data from different stations in a particular city and to transmit the received data to Central Control Server at IITM, Pune.

5. Ambient Air Quality Monitoring Equipment

various instruments are used to monitor ambient air quality such as high-volume sampler, low volume sampler, Dichotomous sampler, respirable dust samplers etc.

A. High volume sampler: High volume sampler is a basic instrument used to monitor airborne particulate matter having diameter less than 10 micrometre. It draws large volume of air which is more than 1500 m³ of air over 24 hours.

B. Low Volume Sampler: Basic difference between high volume sampler and low volume Sampler is amount of air sampled. low volume sampler draws only 24 m³ of air or less.

C. Dichotomous Sampler: The dichotomous air sampler is a dual-filter air sampler for the simultaneous collection of the fine PM_{2.5} and the coarse PM₁₀. 2.5 particles contained within PM₁₀. In this sampler virtual impacted allows to separate aerosol particles based on virtual impaction principle.

D. Respirable Dust Sampler: The primary purpose of personal respirable dust sampling is to characterize (with regard to mass and size) the quality of the ambient air to evaluate a miner's dust exposure. The mass of respirable dust inhaled can be determined by sampling. Their extremely small size also means they can be breathed deep into your lungs and lead to lung damage.

6. Air Pollution Control Devices

A. Mechanical Dust Collectors: mechanical dust collector is defined as a device which separates dust in a dry state from gas through the application of inertial and gravitational forces only. The most widely used type of mechanical dust collector is the cyclone, in which centrifugal force plays the major role in effecting the separation of dust from gas.

B. Electrostatic Precipitators : An [electrostatic precipitator](#) is a type of filter that uses [static electricity](#) to remove [soot](#) and [ash](#) from exhaust fumes before they exit the smokestacks.^[2] Unburned particles of [carbon](#) in smoke are pulled out of the smoke by using static electricity in the precipitators, leaving clean, hot air to escape the smokestacks.^[2] It is vital to remove this unreacted carbon from the smoke, as it can damage buildings and [harm human health](#) - especially respiratory health.

C. Cyclone Separators : A [cyclone separator](#) is a separation device that uses the principle of [inertia](#) to remove particulate matter from flue gases.^[3] In these separators, dirty flue gas enters a chamber containing a vortex, similar to a tornado. Because of the difference in inertia of gas particles and larger particulate matter, the gas particles move up the cylinder while larger particles hit the inside wall and drop down. This separates the particulate matter from the flue gas, leaving cleaned flue gas.

D. Bag House : A baghouse, also known as a baghouse filter, bag filter, or fabric filter is an [air pollution control](#) device and [dust collector](#) that removes [particulates](#) or gas released from commercial processes out of the air.

7. Conclusion:

Various researches have been conducted to analyse the change in air quality parameters with change in climatic conditions. Environmental monitoring methods are used according severity of polluted zones, thus this work is an attempt to assess available research studies on ambient air quality. A review of various researches reveals data with a specific focus on particular areas. Review study shows that there is a large contribution from industrial activities, transportation and dust in the ambient air.

References:

1. Anil Kumar Singhdeo and Nilamadhab Suna, "Monitoring Of Sulphur Dioxide, Nitrogen Oxides, Pm10 And TSP Present In The Ambient Air Of NIT, Rourkela, A Thesis Submitted In Partial Fulfillment Of The Requirements For The Degree Of Bachelor Of Technology in Civil Engineering, 1-92
2. Ashok Kumar. (July 24, 2015). Air Pollution Control Devices [Online]. Available: http://www.eng.utoledo.edu/~akumar/IAP1/Pollution_%20Control.htm
3. Avnish Chauhan, Mayank Pawar, Rajeev Kumar and P. C. Joshi, "Ambient Air Quality Status in Uttarakhand (India): A Case Study of Haridwar And Dehradun Using Air Quality Index" in Journal of American Science 2010;6(9).
4. CPCB (2009), National Ambient air quality standards, central pollution control board, ministry of environment and forest, govt. of India, Notification New Delhi, 18th Novembers

-
5. C.S. Kapoor, B. R. Bamniya, Smita Jain, K.Kapoor, " Status and Monitoring of Ambient Air Quality of 'Cityof Lakes' Udaipur, (Raj.) India" in Research in Health and Nutrition (RHN)Volume 1 Issue 1, October 2013.
 6. Diagi, B. , Suzan, A. , Nnaemeka, O. , Ekweogu, C. , Acholonu, C. and Emmanuel, O. (2022) An Assessment of Vehicular Emission in the Vicinity of Selected Markets in Owerri, Imo State, Nigeria.
 7. Hannah Ritchie (2019) - "Outdoor Air Pollution". Published online at OurWorldInData.org. Retrieved from: '<https://ourworldindata.org/outdoor-airpollution>'
 8. Pandey V., Dohare D., (2016), Assessment of present ambient air quality of Indore city using Indian air quality index - a case study, IJSTE - International Journal of Science Technology & Engineering, 3(6): 153-157
 9. Roy, S., Biswas, S. P., Mahata, S., & Bose, R. (2018, October). Time series forecasting usingexponential smoothing to predict the major atmospheric pollutants. In 2018 International Conference on Advances in Computing, Communication Control and Networking (ICACCCN) (pp. 679-684). IEEE.
 10. Sharma, A., & Peshin, S. K. (2014). Study of air pollution trends at Lodhi road, New Delhi through online monitoring. International Journal of Environmental Sciences, 5(2), 217-235
 11. Sharma, M., Pandey, R., Maheshwari, M., Sengupta, B., Shukla, B. P., Gupta, N. K., & Johri, S. (2003). Interpretation of air quality data using an air quality index for the city ofKanpur, India. Journal of Environmental Engineering and Science, 2(6), 453-462.