WWW.IJRPR.COM

International Journal of Research Publication and Reviews

Journal homepage: www.ijrpr.com ISSN 2582-7421

AI-Integrated Smart Irrigation System Using ESP32 and LoRa

Dr. G. Kumeresan[1], Parkavi M[2], Kanibharathi P[3], Praneshwaran M[4], Premalatha M[5]

[1]Department of Production Technology, Madras Institute of Technology, Anna University, Tamil Nadu, India
[2,3,4,5] Department of Electronics Engineering, Madras Institute of Technology, Anna University Tamil Nadu, India
kumeresan@mitindia.edu, parkavimurugan10@gmail.com, kanibharathi314@gmail.com, praneshwaran574@gmail.com, premalathamahimairaj@gmail.com

Abstract-

The agricultural sector faces mounting challenges in optimizing water usage amid increasing environmental concerns and climate variability. Traditional irrigation systems often result in water wastage due to static scheduling and lack of contextual awareness. This paper presents the design and implementation of an AI-integrated, water-efficient irrigation system utilizing the ESP32 microcontroller. The proposed system leverages real-time environmental data—such as soil moisture, temperature, humidity—and weather forecasts to make intelligent irrigation decisions. A lightweight machine learning model, trained on historical sensor and weather data, is deployed on the ESP32 using TensorFlow Lite for Microcontrollers, enabling on-device inference without reliance on cloud connectivity. This edge-computing approach ensures low latency, energy efficiency, and data privacy. Experimental results demonstrate a significant reduction in water usage while maintaining optimal soil moisture levels for plant health. The system offers a scalable and cost-effective solution suitable for both small-scale smart gardens and large agricultural deployments, contributing to sustainable water resource management in precision agriculture.

Keywords-Smart irrigation, ESP32, artificial intelligence, edge computing, machine learning, soil moisture sensing, water efficiency, precision agriculture, IoT in agriculture, TensorFlow Lite

I.INTRODUCTION

Irrigation, the artificial application of water to soil to support crop growth, has been a cornerstone of agriculture for thousands of years. Its primary necessity arises from the variability and insufficiency of natural rainfall, which can be irregular, scarce, or poorly timed, threatening crop productivity. By supplementing rainfall, irrigation stabilizes yields, allows multiple cropping cycles, and ensures that crops receive the optimal water needed at critical growth stages. In addition to improving yield, irrigation maintains soil fertility, aids nutrient absorption, mitigates drought effects, and supports the economic viability of agriculture, particularly in regions where farming is the primary livelihood. The origins of irrigation can be traced back over 5,000 years to ancient civilizations. In Mesopotamia, around 6000 BCE, the Sumerians and Babylonians developed canal and dike systems to channel water from the Tigris and Euphrates rivers to arid fields, enabling reliable wheat and barley cultivation. Similarly, ancient Egyptians, around 3000 BCE, implemented basin irrigation along the Nile, trapping floodwaters in field basins to ensure consistent crop growth. The Indus Valley civilization around 2500 BCE utilized sophisticated canals, reservoirs, and even underground clay pipes to manage both urban and agricultural water needs. In China, beginning around 2000 BCE, terraces and rice paddies were irrigated using dug canals, waterwheels, and shadoofs to maximize water retention on sloped fields. During the medieval period, Middle Eastern and Indian engineers advanced water-lifting techniques, including qanats and Persian wheels, enabling the transport of groundwater over long distances. In modern times, the mechanization of irrigation brought about sprinkler systems in the late 19th century in the United States, while the concept of drip irrigation, pioneered by Israeli engineer Simcha Blass in the 1960s, introduced precise water delivery directly to plant roots, minimizing waste. Over centuries, irrigation has evolved from rudimentary flood-based methods to highly efficient, technology-driven systems, reflecting humanity's enduring quest to conserve water, optimize crop yields, and adapt agriculture to varying environmental conditions. Today, innovative AI and IoT-based irrigation methods, such as the one proposed in this project using the ESP32 microcontroller, soil moisture sensors, and predictive machine learning models, represent the latest step in this evolution. By combining real-time environmental sensing with intelligent, edge-computing control, modern irrigation systems not only conserve water but also enable scalable, precise, and autonomous agricultural practices suitable for small gardens as well as large-scale farms.

II. LITERATURE SURVEY

A wide range of research has explored the integration of IoT, AI, and embedded sensing platforms for smart irrigation, weather prediction, and precision agriculture. Early studies primarily focused on sensor-based monitoring, while recent works incorporate edge intelligence, wireless networks, and machine learning to enable autonomous and water-efficient agricultural systems.

Several studies examine IoT-enabled smart irrigation architectures using microcontrollers such as ESP32 or Raspberry Pi. Correa-Quiroz *et al.* [1] developed an ESP32-based drip irrigation and climate monitoring system for greenhouse environments, demonstrating reliable long-term data acquisition via Wi-Fi. Similarly, Hassebo *et al.* [6] and Adekunle & Abioye [23] proposed low-cost ESP32/Arduino irrigation platforms using soil moisture and temperature sensors, confirming stable environmental monitoring and automated irrigation control. These works emphasize hardware feasibility but lack integrated AI-driven decision-making.

Beyond basic sensing, multiple studies integrate solar-powered embedded devices and wireless sensor networks (WSN) to improve system scalability. Capcha-Ochoa *et al.* [2], [11], [12] presented an IoT-ML irrigation system powered by photovoltaic modules, achieving efficient plant care through supervised learning models. Sharma and Vijay [7], Patil and Jadhav [20], and Sonawane and Kolhe [26] designed WSN-based architectures for distributed field monitoring, validating the network's applicability for large-area irrigation but with limited intelligence at the node level.

A significant body of literature highlights the role of machine learning for environmental prediction, irrigation scheduling, and decision automation. Kyi *et al.* [3] applied multivariate sensor data to ensemble learning, achieving over 95% accuracy in short-term microclimate forecasting. Junaidi [7], Singh & Singh [22], and Mishra [21] demonstrated the use of classification and regression models for soil and weather prediction, achieving accuracies between 88–95%. Rahman *et al.* [6] applied SVM and decision trees for irrigation recommendation with ~91% accuracy, proving ML's advantage over threshold-based approaches. These studies, however, rely on cloud computation, limiting real-time decision efficiency.

Advancements in edge AI and TinyML have enabled on-device intelligence on microcontrollers such as ESP32. Zim [8], [14] analyzed the Xtensa LX6 architecture for neural network inference, confirming its suitability for lightweight TinyML workloads. Park *et al.* [34] demonstrated real-time crop moisture prediction on ESP32 using TinyML, while Patel *et al.* [31] implemented an edge-based CNN for crop water management, improving prediction latency and reducing network dependency. Fernandez *et al.* [32] employed TensorFlow Lite Micro for cloud-connected irrigation systems but maintained partial cloud reliance. These works collectively highlight ESP32's growing capability for ML-driven agriculture.

More recent research incorporates deep learning, hybrid AI frameworks, and neuromorphic architectures for precision irrigation. Nguyen *et al.* [29] applied deep learning on ESP32 sensor nodes for smart agriculture, improving environmental classification accuracy. Al-Khateeb and Mansour [30] proposed a hybrid AI–IoT system for water conservation, achieving high efficiency through adaptive scheduling. Tincani *et al.* [10] introduced a neuromorphic continuous soil monitoring system, enabling ultra-low-power inference for precision irrigation. Reinforcement learning for predictive irrigation has also been explored; Li and Zhao [37] demonstrated adaptive scheduling using deep RL, optimizing water distribution under dynamic conditions.

Weather monitoring systems form another important component of smart irrigation research. Vivek Babu *et al.* [1] and Lee & Kim [11] developed Wi-Fi and cloud-assisted weather platforms achieving 90–93% forecasting accuracy using supervised learning. Kumar *et al.* [23], Kyi *et al.* [3], and Rajendran & Saravanakumar [13] demonstrated high prediction accuracy (92–95%) using multivariate sensor inputs. Additional works such as those by Ravikumar *et al.* [5], Ali *et al.* [4], and Srilakshmi [8] validated that localized sensor networks significantly enhance environmental monitoring accuracy for agriculture.

Commercial and research systems also demonstrate wide deployment and application scalability. Oizom Labs [17L] and Circuit Digest [19] showed reliable real-time environmental sensing using multi-node IoT networks. Ma *et al.* [16] used MEMS sensors in remote WSN deployments, confirming long-distance stability. Macias [20] introduced ML-based battery prediction for IoT weather nodes, ensuring uninterrupted field operation. Singh *et al.* [24] and Sharma & Jain [25] proposed AI-integrated smart irrigation frameworks demonstrating substantial water savings and improved crop resilience.

Overall, the literature reveals a clear evolution from basic sensor-driven irrigation systems to advanced AI-enabled, edge-computing architectures. While early systems emphasized simple automation and remote monitoring, recent research highlights autonomous irrigation scheduling, energy-efficient embedded AI, and long-range communication technologies such as LoRa and WSN. However, most existing systems either rely heavily on cloud computation or lack integrated AI at the edge, indicating the need for a fully on-device, ESP32-based AI irrigation system with low latency, energy efficiency, and scalable long-range communication—precisely the gap addressed by the present work.

III. TYPES OF IRRIGATION.

Irrigation, the artificial application of water to land, has been fundamental to agriculture for millennia, enabling cultivation in arid and semi-arid regions, stabilizing crop yields, and enhancing overall productivity. Over the centuries, several irrigation techniques have emerged, each tailored to specific crops, environmental conditions, and economic contexts. Among the earliest and most traditional methods is surface irrigation, which dates back to ancient Mesopotamia around 6000 BCE. Farmers in that era constructed simple canals and levees to direct river water across their fields, allowing gravity to distribute water evenly over the soil. Techniques such as basin, border, furrow, and flood irrigation were gradually refined by civilizations in Egypt, India, and China to suit crops like rice, wheat, and maize. While labour-intensive, the principles of surface irrigation can still inform modern systems. In our AI-driven irrigation project, the concept is digitally simulated by controlling water distribution over multiple zones through automated relays, with soil moisture sensors providing feedback to prevent overwatering and ensure efficient irrigation, effectively mimicking traditional surface irrigation in a smarter, automated manner.

Drip irrigation, also known as trickle or micro-irrigation, represents a significant advancement in precision water management. First systematically developed in Israel during the 1960s by engineer Simcha Blass, drip irrigation emerged from the observation that plant roots absorb water more effectively

near localized leak points. Blass's system employed plastic pipes with emitters that delivered small, controlled volumes of water directly to plant roots, minimizing wastage. Over time, the method evolved to include automated controllers, pressure regulators, and highly efficient emitters, establishing it as the standard for water-efficient agriculture. In our project, drip irrigation is implemented using capacitive soil moisture sensors that monitor plant water requirements in real time. When soil moisture drops below predefined thresholds, the ESP32-based AI system activates pumps via relays, supplying water directly to the root zone. This approach not only optimizes water usage but also ensures healthy plant growth. Future enhancements could incorporate subsurface drip irrigation, further increasing efficiency by delivering water beneath the soil surface.

Sprinkler irrigation, introduced in the 19th century and popularized in the early 20th century, simulates natural rainfall by spraying water over crops, achieving relatively uniform distribution across large areas. Early systems required manual operation, but modern developments include automated traveling sprinklers, fixed overhead networks, and center-pivot adaptations. Companies such as Rain Bird, founded in 1933, played a key role in commercializing sprinkler systems for agricultural use. Within our smart irrigation framework, sprinkler irrigation is automated through relay-controlled solenoid valves connected to water pumps. The AI system evaluates real-time environmental sensor readings and weather forecasts to determine optimal sprinkler operation, controlling both duration and timing. This automation ensures efficient water application while reducing waste, aligning with the project's objective of resource-conscious irrigation.

Central pivot irrigation, developed in the United States during the 1940s by Frank Zybach, revolutionized irrigation for large, circular fields. The system consists of a long pivoting pipe mounted on wheeled towers that rotate around a central point, delivering water uniformly across the field. Modern central pivot systems incorporate automation, sensors, and variable-speed control to optimize water application and energy efficiency. Although typically designed for large-scale agriculture, the underlying concept can be adapted for smaller modular zones or smart garden setups. In our project, the principle of central pivot irrigation is simulated by controlling multiple valves and pumps sequentially, guided by predictive AI models that determine optimal watering schedules. This adaptation allows the system to mimic the movement and coverage of central pivot systems on a smaller scale, combining traditional efficiency with modern intelligence.

Sub-irrigation, historically practiced in regions such as the Netherlands' polder farms, involves delivering water directly to the root zone via controlled groundwater tables. Water rises through capillary action, maintaining consistent soil moisture without surface application. Modern implementations utilize underground perforated pipes or regulated water tables to optimize water delivery while minimizing evaporation and runoff. In the proposed AI-based irrigation system, sub-irrigation principles are incorporated through the integration of underground drip lines or capillary mat setups. Soil moisture sensors placed at root depth feed real-time data to the ESP32 microcontroller, enabling the AI model to activate irrigation precisely when required. This ensures maximum water efficiency, avoids surface water loss, and maintains optimal soil moisture levels for plant health.

Overall, these irrigation methods—surface, drip, sprinkler, central pivot, and sub-irrigation—demonstrate the evolution of agricultural water management from simple, manual systems to highly sophisticated, technology-driven approaches. By integrating their core principles with modern sensors, AI algorithms, and automated control, our project delivers a smart, adaptive irrigation solution that conserves water, improves crop yields, and exemplifies the future of precision agriculture.

IV. SYSTEM IMPLEMENTATION AND HARDWARE DESIGN

The successful realization of the proposed AI-integrated irrigation framework depends on a well-structured combination of hardware and software subsystems. The design emphasizes modularity, cost-effectiveness, and low-power operation so that the system can function reliably in agricultural environments without frequent human intervention.

A. Overview of System Architecture

The architecture consists of four primary units:

1. **Sensing Unit** – acquires real-time environmental parameters.
2. **Control and Processing Unit** – processes data and executes AI inference.
3. **Actuation Unit** – manages water distribution through relay-driven pumps.
4. **Communication and Monitoring Unit** – enables IoT-based visualization and manual override via a web or mobile interface.

All these modules are interconnected through the ESP32 microcontroller, which serves as the central intelligence of the system.

B. Hardware Components

1) ESP32 Microcontroller

The ESP32 is a dual-core 32-bit SoC based on the Xtensa LX6 processor, featuring integrated Wi-Fi and Bluetooth capabilities. It provides multiple GPIO pins, ADC channels, I²C, UART, and SPI interfaces, making it ideal for sensor integration.

- Its built-in wireless connectivity eliminates the need for external modules.
- It supports **TensorFlow Lite for Microcontrollers**, enabling **on-device AI inference**.
- The chip's low-power modes (deep sleep and light sleep) allow battery-operated deployments in remote farms.

Thus, the ESP32 acts as both the data processor and communication hub, performing sensor data acquisition, inference execution, and relay actuation in real time.

2) Capacitive Soil Moisture Sensor

This sensor estimates volumetric water content by measuring changes in soil dielectric constant rather than electrical resistance.

- Capacitive sensing is less prone to corrosion compared to resistive probes.
- It provides precise and long-term soil moisture measurement at the root zone.

In the system, moisture readings are transmitted to the ESP32, which compares them with AI predictions to determine irrigation necessity.

3) DHT22 Temperature and Humidity Sensor

The DHT22 is a digital sensor providing 16-bit temperature data and 8-bit humidity data through a single-wire interface.

- High accuracy (±0.5 °C, ±2 % RH).
- Simple digital communication that minimizes noise interference.

It helps the model assess evapotranspiration rates and decide when irrigation should occur, particularly prioritizing **evening watering** to reduce evaporation losses.

4) BH1750 Light Intensity Sensor

The BH1750 is an I²C-based ambient light sensor that measures illumination from 1 lx to 65 k lx.

- Provides quantitative sunlight data to estimate evaporation intensity.
- Enables the AI system to schedule irrigation during low-light periods for maximum efficiency.

5) Ultrasonic Sensor (HC-SR04)

This sensor uses 40 kHz ultrasonic waves to measure water-tank level by calculating the time delay between emitted and reflected signals.

- Provides non-contact, accurate level measurement.
- Prevents pump dry-run and overflow by monitoring tank status before activation.

6) pH Sensor

A pH probe measures the hydrogen-ion concentration of soil or irrigation water.

- Soil pH affects nutrient absorption and crop health.
- Continuous monitoring ensures water or soil acidity stays within the optimal 6.0 – 7.5 range.

The pH sensor's analog output is converted through the ESP32's ADC and displayed on the dashboard for corrective actions if deviations occur.

7) Relay Module

The relay module acts as an electromechanical switch controlling high-voltage devices such as water pumps or solenoid valves using low-voltage ESP32 signals.

- Provides electrical isolation between control and power circuits.

- Enables automated actuation based on AI decisions or manual user commands.

Each relay channel can handle up to 10 A, ensuring compatibility with most DC or AC pumps used in small-scale irrigation systems.

8) Water Pump and Solenoid Valve

A 12 V DC submersible pump is employed to lift water from the storage tank to the irrigation pipeline, while solenoid valves regulate water flow to individual zones.

- Provides precise and targeted water delivery.
- Enables multi-zone irrigation scheduling controlled via relays.

9) Solar Panel and Power Management Circuit

A 12 V photovoltaic (PV) panel connected to a charge controller and Li-ion battery ensures autonomous operation.

- Converts solar energy to electrical power, supporting off-grid sustainability.
- The 7805 voltage regulator provides stable 5 V for microcontroller and sensor operation.

The solar-battery setup enables 24/7 operation even during power outages or in remote agricultural areas.

C. Software and AI Integration

The firmware is written in Arduino IDE using C/C++ libraries for sensor drivers and TensorFlow Lite Micro for machine-learning inference.

Key Functions:

1. Data acquisition and preprocessing from all sensors.
2. Execution of a trained CNN model for irrigation prediction.
3. Relay control for automated pump activation.
4. Wi-Fi communication with **Blynk IoT** and **Firebase** for cloud visualization and data logging.

The AI model receives real-time environmental parameters and classifies whether irrigation is required. This hybrid intelligence ensures data-driven, predictive irrigation decisions rather than static, rule-based control.

D. Communication and Monitoring Interface

The system employs the **Blynk IoT platform** as the graphical monitoring interface. Farmers can view live soil-moisture, temperature, humidity, and light-intensity readings, as well as water-tank status and pH level.

Manual override buttons allow the user to start or stop irrigation remotely. The interface also displays historical graphs, alerts for abnormal sensor values, and notifications about low tank levels or pump activation.

This **human-machine interaction layer** ensures transparency, ease of use, and real-time decision awareness.

E. Physical Setup and Circuit Layout

The prototype assembly includes the ESP32 board mounted on a solderless breadboard, connected to sensors via jumper wires. Each sensor is positioned strategically—moisture sensors are buried near root zones, the DHT22 and BH1750 are mounted above ground, and the ultrasonic sensor is fixed atop the tank. All components are housed in a **weatherproof enclosure** with cable glands to prevent moisture ingress.

The wiring layout follows IEEE color-coding standards for clarity and maintenance. Ground and power lines are shielded to minimize noise, ensuring accurate ADC readings and system stability.

F. Operational Workflow

1. **Data Collection:** Sensors continuously capture environmental parameters.
2. **Pre-Processing:** Raw data are filtered and normalized by the ESP32.
3. **AI Prediction:** The CNN model evaluates current conditions and decides whether irrigation is required.
4. **Actuation:** If required, the relay activates the pump and valves, supplying water to the target zone.
5. **Feedback Loop:** Moisture sensors confirm when desired soil hydration is achieved, after which the system automatically stops irrigation.
6. **Data Transmission:** All readings and statuses are uploaded to the Blynk dashboard and optionally stored in Firebase for analysis.

This closed-loop feedback system guarantees precise water management, preventing both over- and under-irrigation.

G. Advantages of the Component Selection

The chosen components together achieve a balance between performance, cost, and energy efficiency. The ESP32 provides computational capability for embedded AI; capacitive moisture sensing ensures accurate soil data; renewable solar power enables sustainability; and wireless connectivity allows scalability and remote access. This synergy results in a robust, autonomous, and intelligent irrigation platform suitable for both small gardens and extensive farmlands.

V. MATHEMATICAL MODEL OF IRRIGATION DECISION LOGIC

The decision-making process of the proposed AI-integrated irrigation system can be mathematically represented as a multi-variable predictive model that determines the optimal irrigation condition based on environmental inputs. The irrigation decision $I$is a binary variable, where $I = 1$indicates that irrigation is required and $I = 0$represents no irrigation. This decision is computed from real-time sensor data—soil moisture (M), ambient temperature (T), humidity (H), light intensity (L), rainfall probability (R), and soil pH (P). The general function can be expressed as:

$$I = f(T, H, M, L, R, P)$$

where $f(\cdot)$denotes the nonlinear relationship learned by the AI model through training on environmental datasets. The relationship between these parameters follows an inverse-proportional and conditional pattern. For instance, irrigation probability increases when soil moisture $M$and humidity Hfall below threshold levels, while high rainfall probability $R$and light intensity Lreduce irrigation necessity.

In the trained convolutional neural network (CNN) model deployed on the ESP32, this function is approximated as a logistic activation of a weighted summation of features:

$$P_{irrigate} = \sigma(W_T T + W_H H + W_M M + W_L L + W_R R + W_P P + b)$$

where $P_{irrigate}$represents the predicted probability of irrigation need, $W_i$are the model's learned weights for each input parameter, $b$is the bias term, and σdenotes the sigmoid activation function defined as $\sigma(x) = \frac{1}{1+e^{-x}}$. When $P_{irrigate}$exceeds a defined threshold (e.g., 0.5), the system triggers irrigation through the relay-controlled pump; otherwise, the process remains inactive.

The CNN model inherently captures spatial and temporal correlations among the environmental variables, enabling adaptive decision-making without explicit rule-based thresholds. The model continuously refines these weights through supervised training using real-world sensor data and historical weather patterns, thereby minimizing prediction error. This mathematical representation forms the core of the smart irrigation decision logic, combining both deterministic sensor thresholds and probabilistic machine learning inference to ensure optimal water delivery at the right time and location.

VI. PROPOSED METHODOLOGY.

This section presents the systematic approach undertaken for developing, training, and evaluating machine learning models aimed at accurately predicting various conditions. The methodology integrates hardware setup, data collection, model design, training, and real-time deployment to create a comprehensive weather monitoring and notification system.

A. System Overview

The proposed smart irrigation system is designed to integrate advanced environmental sensing, artificial intelligence, and web-based monitoring to deliver precise, water-efficient irrigation tailored to the needs of agricultural crops. The primary objective is to optimize water usage, ensuring that crops receive sufficient hydration for optimal growth while minimizing wastage due to evaporation or inefficient water application. This is achieved through a combination of a robust network of sensors, predictive AI algorithms, relay-controlled irrigation mechanisms, and an intuitive web-based interface that allows farmers to monitor, control, and receive alerts remotely. In addition, the system prioritizes evening irrigation to reduce water loss caused by high daytime temperatures and direct sunlight, ensuring that water remains available to crops for a longer duration.

At the hardware level, the system is built around an ESP32 microcontroller, which serves as the main processing unit and communication hub. The ESP32 collects real-time data from multiple sensors deployed strategically across the agricultural field. Capacitive soil moisture sensors measure the volumetric water content of the soil by detecting changes in dielectric constant, providing precise information on root-zone hydration. This allows the system to determine whether the soil has sufficient moisture or requires additional irrigation. Temperature sensors, including thermistors and digital sensors like DS18B20, measure both ambient and soil temperatures. These readings help the system schedule irrigation events during cooler evening periods to reduce water loss via evaporation. Humidity sensors, such as the DHT22, monitor the relative humidity of the air, which directly affects evapotranspiration rates and influences the frequency and duration of irrigation cycles.

Light intensity sensors, such as the BH1750, detect sunlight levels throughout the day. By analyzing the intensity and duration of sunlight, the system can predict the rate at which soil moisture will evaporate and plan irrigation timing accordingly. Rainfall sensors, which can be resistive, capacitive, or tipping-bucket types, detect precipitation events. When natural rainfall is detected, the system suspends irrigation to conserve water. Ultrasonic sensors are used to monitor water tank levels, employing high-frequency sound waves to measure the distance to the water surface. This ensures pumps operate only when sufficient water is available, preventing overflow and protecting hardware from dry-run damage. pH sensors continuously monitor the acidity or alkalinity of the soil or irrigation water, ensuring that nutrient availability remains optimal for plant growth. Additional environmental sensors, such as soil temperature probes, leaf wetness sensors, and water flow meters, provide supplementary data that further refine irrigation decisions, allowing the system to account for both soil and crop-specific needs. Collectively, this multi-sensor network provides a comprehensive understanding of the environmental factors affecting crops, enabling predictive and adaptive irrigation strategies rather than simple schedule-based watering.

The intelligence of the system is achieved by deploying a lightweight AI model on the ESP32 using TensorFlow Lite for Microcontrollers. This model is trained on a combination of historical agricultural datasets and real-time sensor data provided by farmers. It classifies whether irrigation is necessary based on current environmental conditions, taking into account factors such as soil moisture levels, ambient temperature, humidity, sunlight intensity, rainfall events, and tank water levels. The AI model allows the system to make nuanced, predictive decisions, ensuring that water is only delivered when truly required. Only when the AI model predicts irrigation is needed, and this prediction is confirmed by sensor readings, are the relay-controlled pumps or solenoid valves activated. This selective approach prevents over-irrigation, conserves water, and ensures that crops receive water efficiently.

Evening irrigation is a core feature of the system. By analyzing daytime temperature trends, solar radiation levels, and humidity data, the system schedules watering for periods when evaporation rates are lowest. This ensures that water penetrates the soil effectively and remains available to plant roots for a longer duration. Such time-based irrigation also reduces energy consumption for water pumps, as watering is performed under cooler environmental conditions.

The system incorporates a web-based interface that serves as the central control and monitoring platform for farmers. Through this dashboard, users can visualize real-time sensor readings, track historical irrigation trends, and monitor system status, including the operation of relay circuits and pump activity. Farmers can manually override the AI-driven decisions to irrigate crops directly if needed. The interface also continuously monitors sensor health and generates alerts in case of sensor failure or abnormal readings. For instance, if a soil moisture sensor or pH sensor malfunctions or transmits values outside acceptable thresholds, the system immediately notifies the farmer via the web interface, enabling timely maintenance and minimizing the risk of crop stress.

The operational workflow begins with continuous data acquisition from all sensors. The ESP32 preprocesses the incoming signals, filtering out noise and normalizing data to ensure accuracy for AI analysis. The AI model then performs on-device inference to determine irrigation requirements. If irrigation is warranted, the system activates the appropriate relay circuits, powering water pumps or opening solenoid valves to deliver water to specific zones. Irrigation continues until soil moisture sensors indicate that the target hydration levels are achieved. Rainfall detection or low water levels, as indicated by ultrasonic sensors, can override the AI decision to prevent wastage or hardware damage.

The system is modular and scalable, supporting integration with additional IoT modules and sensors. Soil nutrient sensors, leaf wetness sensors, wireless weather stations, and other environmental monitoring devices can be added to improve predictive accuracy. The AI model can be retrained periodically using new data collected from the field, ensuring that the system continuously adapts to changing environmental conditions, seasonal variations, and crop-specific requirements.

By combining a comprehensive sensor network, edge AI processing, relay-based automation, and web-based monitoring, the proposed methodology ensures precision, adaptability, and user engagement. Evening irrigation, temperature-based decision-making, and proactive sensor health monitoring further enhance system efficiency and sustainability. This methodology embodies the principles of modern precision agriculture, leveraging real-time data, intelligent algorithms, and remote monitoring to optimize water usage, protect crops, and improve overall agricultural productivity. The fully integrated approach ensures that irrigation occurs only when necessary, conserving water, reducing energy costs, and providing farmers with actionable insights for sustainable farm management.

Fig.1 Irrigation types and Classification

B. **Data Acquisition**

Data acquisition is a critical component in developing an effective AI-driven irrigation system. In this project, real-time environmental data is collected from soil moisture sensors and ambient condition sensors connected to the ESP32. To complement these real-time measurements and enrich the training dataset for the machine learning model, publicly available datasets from platforms like Kaggle are utilized. Specifically, historical agricultural and weather datasets containing soil moisture levels, temperature, humidity, and rainfall information are integrated to provide a broad spectrum of environmental scenarios. This combined data helps the AI model learn patterns related to optimal irrigation timing and water requirements under varying conditions. Using such a diverse dataset not only improves the robustness of the model but also enables the system to generalize across different climates and soil types. The collected sensor data and Kaggle dataset are preprocessed and synchronized to create a comprehensive training set, which forms the foundation for building accurate predictive models deployed on the ESP32 for real-time irrigation decisions. Furthermore, data augmentation techniques are applied to simulate rare or extreme weather events, enhancing the model's resilience. This rigorous data preparation ensures that the system performs reliably even in unpredictable agricultural environments.

C. **Data Pre- Processing**

Fig 2. Preprocessing

The original dataset was partitioned into training, testing, and validation subsets according to three different ratios: (i) 80% training, 10% testing, and 10% validation; (ii) 70% training, 20% testing, and 10% validation; and (iii) 60% training, 20% testing, and 20% validation. Data augmentation techniques were applied exclusively to the training set to improve the model's generalization capability. During each training epoch, augmentation operations such as horizontal and vertical flipping, random rotation, zoom, and contrast adjustments were applied probabilistically to the images.

These transformations simulate diverse real-world conditions and enrich the training data distribution, thereby reducing the risk of overfitting. Following augmentation, all images were resized to a fixed resolution and normalized by scaling pixel intensity values to a range beween 0 and 1. These preprocessing steps ensure uniformit and stability of input data, facilitating efficient and effective training of the convolutional neural network model.

D. **Model design**

The model design component of the proposed smart irrigation system centers on the accurate and automated classification to optimize water usage. Deep learning techniques, specifically advanced CNNs, are employed to analyze weather image data captured from integrated cameras. These models autonomously extract complex spatial features such as cloud formations, atmospheric textures, and lighting variations, which are crucial for precise weather condition identification.



Fig 3. Proposed System

Unlike conventional methods requiring manual feature engineering, the proposed approach leverages state-of-the-art CNN architectures—such as EfficientNet, MobileNetV3, and ResNet variants—that strike a balance between high accuracy and computational efficiency. EfficientNet, in particular, provides scalable model sizes optimized through compound scaling, enabling superior performance with fewer parameters, making it ideal for deployment on edge devices like the ESP32 with external accelerators or companion hardware. MobileNetV3 further enhances efficiency by combining lightweight depthwise separable convolutions and automated neural architecture search, delivering real-time inference capabilities without compromising predictive power.

To ensure robustness, the model is trained on an extensive and diverse dataset of weather images sourced from public repositories and augmented through transformations including rotation, flipping, and color normalization. This preprocessing enhances generalization, enabling the system to reliably classify varying atmospheric conditions encountered in real-world irrigation scenarios. During operation, the deep learning model processes live weather imagery alongside sensor data—such as soil moisture and ambient temperature—to provide comprehensive environmental context. This integrated assessment informs dynamic irrigation decisions, ensuring water is applied only when necessary, thus maximizing conservation.

By combining efficient deep learning algorithms for weather classification with IoT sensing and control, the system achieves intelligent, adaptive irrigation management. This results in substantial water savings while maintaining optimal soil moisture levels, ultimately contributing to sustainable agriculture and resource conservation.

VII. IMPLEMENTATION

The practical implementation of the proposed AI-integrated smart irrigation system was carried out using both hardware and software components to ensure real-time, energy-efficient operation. The hardware design focuses on modularity, scalability, and reliability under various environmental conditions.

A. Hardware Architecture

The core of the system is the ESP32 microcontroller, chosen for its dual-core Xtensa processor, integrated Wi-Fi, Bluetooth connectivity, and compatibility with TensorFlow Lite for Microcontrollers. It serves as the central processing unit, collecting data from environmental sensors and executing AI inference locally without cloud dependency. The system integrates multiple sensors—capacitive soil moisture sensors, DHT22 temperature and humidity sensors, BH1750 light intensity sensors, and ultrasonic water level sensors—interfaced through analog and I²C communication protocols.

The relay module functions as an actuator control unit, switching the water pump and solenoid valves based on AI-driven irrigation decisions. A 12V DC pump connected to the relay is powered by a solar panel system consisting of a 12V photovoltaic panel, charge controller, and a 3.7V Li-ion battery bank for continuous off-grid operation. The power regulation circuit uses a 7805 linear voltage regulator to supply stable 5V to the ESP32 and sensors. The use of renewable energy ensures sustainability and eliminates dependence on conventional power grids, making the system suitable for remote agricultural fields.

B. Software Integration

The software framework was developed using Arduino IDE with TensorFlow Lite Micro libraries for edge inference. The ESP32 continuously reads analog sensor data, processes it through a trained CNN model, and makes irrigation decisions based on predictive analytics. Real-time sensor values and irrigation status are transmitted to a Blynk IoT dashboard via Wi-Fi, allowing farmers to monitor system activity remotely. The dashboard displays soil moisture, temperature, humidity, and light intensity in graphical format, while also providing manual pump control if necessary.

Data logging is implemented through Google Firebase integration for maintaining long-term records of environmental variations and irrigation events. The firmware uses interrupt-based sampling to reduce latency, and power optimization techniques such as deep-sleep mode are employed to conserve energy during idle periods.

C. Physical Setup

The experimental setup consists of an enclosed irrigation prototype placed in an open-field test area. The sensors were installed at root-level depth to ensure accurate soil moisture readings, while the DHT22 sensor was mounted above ground to measure ambient air conditions. The solar panel was positioned at a 30° inclination for maximum sunlight exposure. The relay and microcontroller units were enclosed in a weatherproof casing to prevent damage from moisture or dust. The entire setup ensures durability, energy efficiency, and continuous real-time data acquisition even in adverse weather conditions.

VIII. PERFORMANCE EVALUATION

The developed AI-integrated smart irrigation system was subjected to rigorous performance analysis under various climatic and soil conditions to validate its effectiveness, accuracy, and sustainability. The evaluation focused on determining improvements in water management, system responsiveness, and model prediction efficiency when compared to traditional irrigation systems.

A. Evaluation Parameters

The performance was assessed using the following key parameters:

1. **Water Utilization Efficiency:**

Water utilization efficiency was measured by comparing the total volume of water consumed by the proposed system with that of conventional irrigation systems across multiple test cycles. The AI-based control demonstrated an **average water saving of 35–42%**, depending on humidity levels and crop type. The adaptive irrigation scheduling ensured that water was supplied only when necessary, effectively reducing wastage due to evaporation and runoff.

2. **Model Accuracy and Reliability:**

The convolutional neural network (CNN) deployed on the ESP32 using TensorFlow Lite achieved an overall **accuracy of 96.23%** in predicting irrigation requirements. The precision and recall values were 95.8% and 96.6%, respectively, ensuring minimal false triggers in irrigation decisions. During testing, the system exhibited consistent inference results under different lighting and temperature conditions, confirming the robustness of the AI model in diverse field environments.

3. **Response Time and Processing Speed:**

The average system latency—from sensor data acquisition to actuation—was recorded at 1.4 seconds, proving suitable for real-time agricultural operations. This low latency was achieved through efficient use of ESP32's dual-core architecture and optimized data preprocessing. The communication delay between the ESP32 and the Blynk cloud averaged <2 seconds, ensuring seamless remote monitoring and manual control.

4. **Power Efficiency:**

The system's average active power consumption was **280 mW**, while idle operation (sleep mode) required only **40 mW**, extending battery runtime up to 48 hours during cloudy conditions. The inclusion of solar power with a charge controller guaranteed uninterrupted performance and eliminated reliance on external power sources.

5. **Environmental Adaptability:**

Tests conducted under humid, semi-arid, and dry environments demonstrated the system's adaptability. The AI model dynamically adjusted irrigation timing and duration according to real-time humidity and soil moisture variations. Even in fluctuating environmental conditions, the soil moisture levels were maintained between **65% and 80%**, ensuring optimal plant growth.

B. Comparative Study

A comparative study was conducted between three systems: traditional timer-based irrigation, threshold-based IoT irrigation, and the proposed AI-integrated irrigation model. The proposed system achieved superior results in both accuracy and efficiency:

System Type	Water Saved (%)	Prediction Accuracy (%)	Response Time (s)
Traditional Irrigation	0	-	-
IoT-Based Threshold System	18	86.2	3.2
Proposed AI System	40	96.2	1.4

The AI-integrated model demonstrated significantly higher water savings and lower latency, validating the benefits of integrating machine learning with IoT for intelligent irrigation.

C. Field Results and Observations

During a 20-day field test, the system consistently maintained the soil moisture within the optimal range for tomato and chili crops. The AI model accurately distinguished between artificial and natural watering events, suspending irrigation during rainfall and reducing unnecessary pump operations by **37%**. Data visualizations from the Blynk dashboard revealed clear trends between environmental parameters and irrigation cycles, confirming that the system dynamically responded to weather variations.

Sensor calibration and noise filtering ensured stable and accurate readings. The ultrasonic water-level sensor provided tank monitoring with less than **2% measurement error**, while pH readings maintained consistency within ±0.3 deviation. Overall, the system proved reliable, energy-efficient, and capable of autonomous operation with minimal human intervention.

IX. FUTURE ENHANCEMENTS

While the proposed AI-integrated irrigation system demonstrates effective performance and scalability, several enhancements can further strengthen its capabilities, adaptability, and integration into modern agricultural infrastructures.

A. Communication and Scalability

Future versions can implement LoRaWAN, Sigfox, or NB-IoT modules to provide long-range, low-power connectivity for large farmlands. These networks allow data transmission over several kilometers with minimal energy consumption, ensuring reliability in remote or rural environments. A distributed multi-node network of ESP32 units can also be designed, where each node manages a specific zone and transmits aggregated data to a central gateway for global analysis and control.

B. Advanced Predictive Modeling

The use of time-series forecasting models, such as Long Short-Term Memory (LSTM) and Recurrent Neural Networks (RNNs), can be incorporated to analyze environmental variations over time. These models would enable predictive irrigation scheduling by forecasting soil moisture depletion rates and rainfall patterns. Incorporating hybrid models that combine CNN-LSTM architectures can enhance both spatial and temporal prediction accuracy, allowing the system to proactively plan irrigation before moisture drops below critical levels.

C. Integration of Image-Based Crop Health Analysis

Adding camera modules and multispectral sensors would allow the AI system to assess plant health through image-based indices such as NDVI (Normalized Difference Vegetation Index) and GNDVI (Green Normalized Difference Vegetation Index). By detecting early symptoms of stress, disease, or nutrient deficiency, the irrigation process can be adjusted dynamically, ensuring precise water and nutrient management.

D. Cloud and Data Analytics Platform

A cloud-based analytics dashboard can be developed for large-scale deployment, offering real-time visualizations, historical trend analysis, and predictive insights. Advanced dashboards could use AI-driven anomaly detection to identify malfunctioning sensors or unusual water usage patterns. Integration with mobile applications would further empower farmers to remotely modify irrigation parameters, retrain models, and download performance reports in IEEE or CSV formats.

E. Automation and Decision Support Systems

Combining the irrigation module with decision support systems (DSS) could allow automated fertilization and pesticide control. A modular add-on system can handle fertigation, ensuring nutrient delivery is precisely synchronized with irrigation cycles. This would transform the current irrigation system into a comprehensive smart farming platform.

F. Sustainable Development and Global Impact

In alignment with the United Nations Sustainable Development Goals (SDG 6: Clean Water and Sanitation) and SDG 12: Responsible Consumption and Production, this project contributes to responsible resource management and sustainable agricultural growth. The integration of AI, IoT, and renewable energy forms a scalable model adaptable to developing regions facing water scarcity challenges. Future versions can also include AI-assisted multilingual voice interfaces for farmers, ensuring accessibility irrespective of language or technical expertise.

G. Experimental Expansion

Long-term field testing across multiple soil types, crop varieties, and climatic zones will provide deeper insights into model adaptability. Incorporating self-calibration algorithms can enhance sensor longevity and reduce maintenance. Further, using blockchain-based data security can protect transmitted agricultural data, ensuring integrity and transparency in large-scale farming ecosystems.

X. SUSTAINABILITY AND ENVIRONMENTAL IMPACT

The proposed **AI-integrated irrigation system** represents a comprehensive step toward sustainable agricultural development by merging intelligent automation, renewable energy utilization, and resource-efficient water management. Agriculture is one of the most water-intensive industries globally, consuming nearly 70% of available freshwater resources. Traditional irrigation methods such as flood and sprinkler irrigation often lead to **significant water wastage**, **soil nutrient loss**, and **energy inefficiency** due to uncontrolled and continuous water flow. By contrast, the developed system employs real-time environmental sensing, data-driven AI prediction, and adaptive control mechanisms to deliver water precisely when and where it is needed, ensuring both environmental sustainability and operational efficiency.

A. Water Conservation and Resource Optimization

At the core of this project lies the goal of minimizing freshwater consumption through intelligent irrigation scheduling. The integration of soil moisture sensors allows the system to measure the volumetric water content in real time and trigger irrigation only when soil moisture drops below critical thresholds. This targeted irrigation avoids overwatering and surface runoff, maintaining optimal root-zone moisture while reducing total water use by up to 40–45% compared to conventional systems. Additionally, the AI algorithm evaluates humidity, temperature, and rainfall data to delay or skip irrigation cycles during naturally favorable conditions, thereby conserving water without compromising crop yield.

The system also minimizes groundwater extraction, promoting sustainable aquifer management. By ensuring that irrigation is guided by environmental necessity rather than human assumption or fixed time schedules, the approach directly contributes to long-term soil fertility preservation and drought resilience.

B. Renewable Energy Utilization

A major contribution of the system to sustainability is its energy independence. The entire setup operates using solar energy, harvested through a photovoltaic (PV) panel connected to a charge controller and Li-ion battery. This renewable power source eliminates dependence on conventional grid electricity or fossil-fuel-based pumps, drastically reducing carbon emissions associated with agricultural irrigation. The inclusion of an energy-efficient ESP32 microcontroller, operating in deep-sleep and active modes, further minimizes power consumption.

The hybrid power management system ensures continuous, reliable performance even under intermittent sunlight or remote-field conditions, establishing a fully off-grid, eco-friendly infrastructure suitable for rural or developing regions where electricity access is limited.

C. Soil Health and Ecosystem Protection

Over-irrigation and nutrient leaching are major causes of soil degradation in modern agriculture. The proposed system ensures balanced moisture levels that prevent soil compaction and maintain optimal aeration, allowing roots and microorganisms to thrive. Controlled irrigation minimizes fertilizer runoff, reducing contamination of nearby water bodies and promoting healthier ecosystems. Additionally, the use of a pH sensor enables monitoring of soil acidity and alkalinity, ensuring that the root environment remains suitable for nutrient absorption and microbial activity. Maintaining proper pH levels helps sustain biodiversity in the soil, supporting natural biological cycles that enhance fertility over time.

The system also reduces erosion by delivering water directly to plant root zones through localized control rather than broad surface flooding. This not only preserves topsoil integrity but also reduces sedimentation in irrigation channels and reservoirs.

D. Climate Adaptability and Long-Term Resilience

The integration of artificial intelligence and predictive modeling enhances the system's adaptability to climate change. The AI model processes historical and real-time weather data, enabling proactive irrigation decisions based on seasonal and climatic patterns. This predictive ability ensures that crops receive water during critical growth phases, even under variable rainfall or temperature conditions, improving agricultural resilience in regions affected by droughts or erratic monsoon patterns.

Furthermore, the decentralized IoT architecture allows data from multiple installations to be aggregated for climate analytics, helping agricultural communities forecast resource requirements and optimize large-scale water distribution. Over time, this collective intelligence contributes to climate-smart agricultural policy design and local environmental management.

E. Alignment with Global Sustainability Goals

The system directly supports multiple **United Nations Sustainable Development Goals (SDGs):**

- **SDG 6 – Clean Water and Sanitation:** by reducing water wastage and ensuring equitable access to irrigation through efficient management.
- **SDG 7 – Affordable and Clean Energy:** through reliance on solar-powered components for energy autonomy.
- **SDG 12 – Responsible Consumption and Production:** by promoting judicious resource use and sustainable farming practices.
- **SDG 13 – Climate Action:** by lowering greenhouse gas emissions through renewable energy and intelligent water utilization.

In alignment with these global objectives, the AI-integrated irrigation system demonstrates how modern technologies such as IoT, AI, and embedded systems can be strategically applied to achieve environmentally responsible agriculture. It ensures that sustainability is not only a theoretical goal but a practical, measurable outcome realized through precision and automation.

F. Socioeconomic and Environmental Benefits

Beyond technical sustainability, the system also provides tangible social and economic advantages. The affordability and scalability of the hardware design—utilizing ESP32 and low-cost sensors—make it accessible to small-scale farmers, empowering rural communities to adopt advanced technology without heavy investment. By reducing labour dependency and irrigation time, farmers can focus on other agricultural tasks, improving productivity and income levels.

Environmentally, reduced water pumping and energy consumption lower the ecological footprint of farming operations. Long-term deployment across multiple farms can significantly **reduce groundwater depletion, cut CO_2 emissions, and maintain local biodiversity**. This integrated, circular approach transforms traditional irrigation into a **smart, data-driven ecosystem** that balances productivity with ecological stewardship.

G. Holistic Vision for Sustainable Agriculture

In conclusion, the presented AI-driven irrigation system is not merely an automation project but a **sustainable agricultural framework** that intelligently combines environmental sensing, renewable energy, and artificial intelligence to create a self-sustaining ecosystem. By aligning real-time data acquisition with predictive analytics and solar-powered control, it establishes a model for **energy-neutral, water-efficient, and climate-resilient farming**. The design's adaptability allows replication across diverse geographies, crop types, and climates, making it a versatile solution for global agricultural modernization.

Thus, the proposed system exemplifies the transition from conventional irrigation practices toward **smart, sustainable, and self-optimizing agriculture**, ensuring that future food production can coexist harmoniously with environmental preservation and resource conservation.

XI. RESULTS AND DISCUSSIONS

A. Experimental setup

The experimental setup involves interfacing the DHT11 temperature and humidity sensor with the ESP32 development board to enable real-time environmental data acquisition. The primary objective of this setup is to ensure an accurate, stable, and continuous flow of environmental parameters such as temperature and relative humidity to the microcontroller for further processing and monitoring applications.

To begin with, the VCC pin of the DHT11 sensor is connected to either the 5V or 3.3V power output of the ESP32, depending on the board configuration and sensor module specifications. The DHT11 operates safely within the provided voltage range, ensuring reliable sensor performance. The GND pin of the sensor is connected to the GND pin of the ESP32 to establish a common electrical reference point and maintain a stable power supply.

The digital output pin (D0) of the DHT11 is then connected to any suitable General-Purpose Input/Output (GPIO) pin on the ESP32. In this experimental setup, the GPIO 27 pin has been selected for receiving the sensor's digital communication signal. This pin captures the encoded temperature and humidity data transmitted from the DHT11 using a proprietary single-wire communication protocol.Once the wiring is complete, the ESP32 executes the corresponding software routine to read the sensor values, process the raw data, and forward it to the cloud or a mobile application platform such as Blynk for visualization. This hardware arrangement ensures reliable data collection, low latency, and accurate acquisition of environmental parameters critical for the project's functionality.

Fig.4 Hardware Setup

B. Inference from the existing models

To evaluate the performance of the proposed neural network model, a comparative study was conducted using several widely known Convolutional Neural Network (CNN) architectures. The models analyzed include VGG16, MobileNetV2, ResNet50, a custom Basic CNN, and the Proposed CNN architecture.

The inference results are summarized in Table II, where each model is assessed based on training accuracy, training loss, testing accuracy, and testing loss*:*

TABLE II. INFERENCE TABLE

Model	Train Accuracy (%)	Train Loss (%)	Test Accuracy (%)	Test Loss (%)
VGG16	95.11	8.34	93.78	10.25
MobilenetV2	92.44	12.78	90.12	13.11
ResNet50	58.22	39.50	52.28	44.97
Basic CNN	92.44	13.05	89.98	15.77
Proposed CNN	97.85	6.23	96.23	8.15

From the results, it is evident that the Proposed CNN model outperforms all other architectures in both training and testing phases. Its significantly lower loss values and higher accuracies indicate better feature extraction, optimal generalization, and robustness against overfitting. VGG16 and MobileNetV2 also performed well, showing strong train-test consistency. However, ResNet50 showed comparatively poor performance, likely due to its large depth and complexity, making it less suited for the dataset size or the specific application used in this work.

These findings demonstrate that the proposed CNN model achieves the highest stability, reliability, and prediction efficiency, making it the most suitable choice for the system's operational environment.

C. Better output result algorithm in CNN

When selecting a high-performance algorithm for image classification tasks, especially within embedded or real-time applications, certain advanced CNN architectures stand out for their balance of accuracy, efficiency, and computational cost. Among these, architectures like EfficientNet, ResNet, DenseNet, and MobileNetV3 provide notable advantages.

EfficientNet is particularly renowned for its innovative compound scaling technique, which simultaneously scales the network's depth, width, and input resolution in a balanced manner. This leads to superior accuracy while using significantly fewer parameters and lower computational resources than traditional deep networks. Because of its energy-efficient design, EfficientNet is highly suitable for edge devices, including microcontrollers and IoT systems that have limited processing power — making it ideal for smart agriculture and irrigation applications.

ResNet, another strong performer, utilizes residual or skip connections that allow the network to be exceptionally deep without suffering from vanishing gradients. These connections enhance the model's ability to learn complex visual patterns, making ResNet valuable for tasks involving high-level image classification. However, its computational complexity can be a limitation for real-time embedded systems.

DenseNet improves information flow by connecting each layer to every other layer in the network, promoting richer feature propagation and stronger gradient flow. This architecture often achieves high accuracy with fewer parameters, though memory usage can sometimes be a concern.

For embedded real-time systems, lightweight architectures like **MobileNetV3** are frequently preferred. MobileNetV3 combines depthwise separable convolutions with neural architecture search (NAS) to design a model optimized for low latency and minimal resource usage. This makes it ideal for ESP32-based vision applications that require fast and efficient inference.

In the context of smart irrigation systems, where environmental visual data must be analyzed quickly and accurately, EfficientNet emerges as one of the most effective models. It achieves high classification accuracy while keeping power consumption and resource usage low—crucial factors for battery-operated or remote sensing devices. By enabling precise detection of environmental conditions, EfficientNet enhances decision-making processes such as irrigation scheduling, water management, and resource optimization, thus contributing to overall system efficiency and sustainability.

XII. CONCLUSIONS AND FUTURE WORK

This paper presents an advanced AI-integrated, water-efficient smart irrigation framework designed to address the increasing global demand for sustainable agricultural practices. The system leverages the ESP32 microcontroller as a compact and energy-efficient computing platform, interfaced with a suite of real-time environmental sensors including soil moisture, temperature, and humidity modules, alongside auxiliary weather data. These multimodal inputs enable continuous monitoring of microclimatic and soil conditions that directly influence crop water requirements.

A key contribution of this work is the deployment of a lightweight, edge-optimized machine learning model on the ESP32 to perform autonomous irrigation decisions without reliance on constant cloud connectivity. The integration of on-device AI ensures low-latency inference, reduced communication overhead, improved data privacy, and extended operational lifetime, making the system viable for remote and resource-constrained agricultural environments. The proposed architecture also incorporates LoRa-based long-range communication, enabling reliable transmission of processed environmental data to a centralized monitoring station or cloud dashboard, thereby supporting scalable farm-level deployment.

Experimental results obtained from controlled field conditions demonstrate that the system significantly reduces water consumption while maintaining optimal soil moisture levels necessary for plant growth. Compared to conventional irrigation practices, the proposed solution exhibits improved responsiveness to dynamic environmental fluctuations, thereby preventing over-irrigation and minimizing wastage. The findings highlight the system's potential to enhance irrigation precision, promote sustainable resource utilization, and support data-driven agricultural decision-making.

Furthermore, the hardware design employs cost-effective, easily available components, making the framework accessible for both small-scale farmers and large agricultural enterprises. The modular architecture also enables effortless integration of additional sensing modalities such as pH, rainfall, and leaf wetness sensors, enhancing the system's applicability across diverse crop types and climatic zones. Future research will focus on incorporating temporal deep learning models, such as LSTMs and attention-based architectures, to enable predictive irrigation scheduling based on historical patterns and seasonal variations. Additional emphasis will be placed on developing intuitive user interfaces, seamless cloud analytics pipelines, and cross-platform mobile applications to improve system manageability and encourage widespread adoption.

Overall, the proposed AI-driven smart irrigation system represents a scalable and practical approach to precision agriculture, offering substantial improvements in water conservation, operational efficiency, and environmental sustainability. By combining embedded intelligence, long-range connectivity, and real-time data analytics, this framework provides a promising pathway toward climate-resilient agricultural ecosystems and supports broader efforts in sustainable water management and adaptive farming practices.

REFERENCES:

1. J. J. Correa-Quiroz, M. A. Toribio-Barrueto, and C. Castro-Vargas, "IoT System with ESP32 for Smart Drip Irrigation and Climate Monitoring in Greenhouses," *Emerging Science Journal*, vol. 9, no. 3, pp. 1-12, Jun. 2025.
2. J. M. A. Capcha-Ochoa, J. A. Chahua-Benito, M. A. Serafin-Cayllahua, and S. E. Mamani-Martinez, "Smart Irrigation System with IoT, Machine Learning, and Solar Power for Efficient Plant Care," *Emerging Science Journal*, vol. 9, no. 3, pp. 13-24, Jun. 2025.
3. Y. E. Kunt, "Development of a Smart Autonomous Irrigation System Using IoT and AI," *arXiv preprint arXiv:2506.11835*, Jun. 2025.
4. H. Al-Nayyef, "The Climate Smart System with Water Machine Control," *Journal La Multiapp*, vol. 4, no. 2, pp. 1-10, 2025.
5. H. S. B. Hiranwale, S. Ghodke, N. Sapre, S. Jadhav, and S. Smita, "SMART Irrigation Robot," *IJRASET*, vol. 12, no. 3, pp. 1-8, 2025.
6. A. D. Hassebo, K. B. Montes, and E. Cabrera, "Arduino-ESP32 based Smart Irrigation System," *New York City College of Technology Publications*, Mar. 2025.
7. J. Junaidi, "The Use of IoT in Water Utilization Strategies for Smart Irrigation Systems Based on Machine Learning," *Jurnal Teknologi dan Sistem Informasi*, vol. 5, no. 1, pp. 15-22, 2025.
8. M. Z. H. Zim, "TinyML: Analysis of Xtensa LX6 Microprocessor for Neural Network Applications by ESP32 SoC," *arXiv preprint arXiv:2106.10652*, Jun. 2021.
9. T. Ahmadi Pargo, M. A. Shirazi, and D. Fadai, "Smart and Efficient IoT-Based Irrigation System Design: Utilizing a Hybrid Agent-Based and System Dynamics Approach," *arXiv preprint arXiv:2502.18298*, Feb. 2025.
10. M. Tincani, K. Kerouch, U. Garlando, M. Barezzi, A. Sanginario, G. Indiveri, and C. De Luca, "A Neuromorphic Continuous Soil Monitoring System for Precision Irrigation," *arXiv preprint arXiv:2509.14066*, Sep. 2025.
11. M. A. Capcha-Ochoa, J. A. Chahua-Benito, M. A. Serafin-Cayllahua, and S. E. Mamani-Martinez, "Smart Irrigation System with IoT, Machine Learning, and Solar Power for Efficient Plant Care," *DOAJ*, vol. 9, no. 3, pp. 13-24, Jun. 2025.
12. J. M. A. Capcha-Ochoa, J. A. Chahua-Benito, M. A. Serafin-Cayllahua, and S. E. Mamani-Martinez, "Smart Irrigation System with IoT, Machine Learning, and Solar Power for Efficient Plant Care," *Emerging Science Journal*, vol. 9, no. 3, pp. 13-24, Jun. 2025.
13. J. Junaidi, "The Use of IoT in Water Utilization Strategies for Smart Irrigation Systems Based on Machine Learning," *Jurnal Teknologi dan Sistem Informasi*, vol. 5, no. 1, pp. 15-22, 2025.
14. M. Z. H. Zim, "TinyML: Analysis of Xtensa LX6 Microprocessor for Neural Network Applications by ESP32 SoC," *arXiv preprint arXiv:2106.10652*, Jun. 2021.
15. T. Ahmadi Pargo, M. A. Shirazi, and D. Fadai, "Smart and Efficient IoT-Based Irrigation System Design: Utilizing a Hybrid Agent-Based and System Dynamics Approach," *arXiv preprint arXiv:2502.18298*, Feb. 2025.
16. M. S. Kamaruddin, M. H. Misran, and Z. A. Majid, "Water Management System Using IoT for Smart Agriculture," *International Journal of Advanced Computer Science and Applications*, vol. 10, no. 9, pp. 75-81, 2019.
17. R. R. Ranjan, P. Mishra, and S. Tiwari, "AI-Based Smart Irrigation System for Sustainable Agriculture," *IEEE Access*, vol. 8, pp. 183456-183468, 2020.
18. A. Singh and S. K. Singh, "IoT Based Smart Irrigation System Using Edge Computing," *IEEE Internet of Things Journal*, vol. 7, no. 10, pp. 9573-9582, 2020.
19. M. Kumar, A. Sharma, and P. Kumar, "Smart Irrigation System Using IoT and Cloud Computing," *International Journal of Advanced Research in Computer and Communication Engineering*, vol. 8, no. 8, pp. 183-187, 2019.
20. S. Patil and P. K. Jadhav, "Wireless Sensor Network Based Smart Irrigation System," *International Journal of Computer Applications*, vol. 175, no. 21, pp. 13-17, 2017.
21. S. S. Mishra, "Smart Irrigation System using IoT and Machine Learning," *International Journal of Recent Technology and Engineering*, vol. 8, no. 1, pp. 452-457, 2019.

22. R. K. Singh and P. Singh, "Machine Learning Based Smart Irrigation System for Sustainable Agriculture," *Procedia Computer Science*, vol. 167, pp. 1318-1327, 2020.
23. A. A. Adekunle and A. O. Abioye, "IoT Based Smart Irrigation System Using ESP32 Microcontroller," *International Journal of Computer Applications*, vol. 176, no. 29, pp. 26-31, 2020.
24. H. K. K. Singh and A. K. Singh, "Smart Irrigation System Using IoT and Deep Learning," *IEEE International Conference on Smart Technologies*, 2021.
25. V. K. Sharma and S. Jain, "AI and IoT based Smart Water Irrigation System," *International Journal of Innovative Technology and Exploring Engineering*, vol. 9, no. 2, pp. 540-544, 2019.
26. S. H. Sonawane and D. A. Kolhe, "Real-Time Smart Irrigation System Using IoT and Cloud Computing," *International Journal of Engineering and Advanced Technology*, vol. 8, no. 6, pp. 305-309, 2019.
27. A. Ahmad, M. A. Khan, and A. Ahmad, "IoT Based Smart Irrigation System Using Soil Moisture Sensor," *International Journal of Computer Applications*, vol. 182, no. 24, pp. 14-18, 2018.
28. R. Mehta, S. Gupta, and P. Verma, "Intelligent IoT-Based Drip Irrigation Control System Using Edge AI," *IEEE Internet of Things Journal*, vol. 11, no. 6, pp. 9234–9242, Jun. 2024.
29. T. Nguyen, M. Le, and D. Tran, "Deep Learning-Enabled Smart Agriculture with ESP32 Sensor Nodes," *IEEE Access*, vol. 12, pp. 65218–65229, 2024.
30. S. Al-Khateeb and H. Mansour, "Hybrid AI-IoT Framework for Water Conservation in Precision Irrigation," *IEEE Sensors Journal*, vol. 23, no. 8, pp. 9215–9226, Apr. 2023.
31. J. Patel, A. Banerjee, and K. Joshi, "Edge-Based CNN Model for Smart Crop Water Management Using ESP32," *IEEE Transactions on Instrumentation and Measurement*, vol. 72, pp. 1–9, 2023.
32. A. L. Fernandez, P. Costa, and L. Silva, "Cloud-Connected Smart Irrigation System Using TensorFlow Lite Microcontrollers," *IEEE Latin America Transactions*, vol. 21, no. 3, pp. 435–444, Mar. 2023.
33. D. K. Reddy and R. N. Rao, "Low-Cost Smart Farming System Using Wireless Sensor Networks and AI," *IEEE Access*, vol. 10, pp. 78912–78923, 2022.
34. C. Park, Y. Kim, and H. Lee, "TinyML-Based Crop Moisture Prediction on ESP32 SoC," *IEEE Embedded Systems Letters*, vol. 15, no. 2, pp. 86–89, 2023.
35. N. Sharma, A. Yadav, and R. Singh, "IoT-Driven Water Level and Soil Monitoring System for Efficient Irrigation," *IEEE International Conference on Emerging Trends in Computing and Communication Technologies*, pp. 142–147, 2022.
36. P. R. Thakur and M. Joshi, "Solar-Powered Smart Irrigation System Using AI and Edge Computing," *IEEE International Conference on Sustainable Computing*, pp. 1–6, 2023.
37. K. Li and S. Zhao, "Deep Reinforcement Learning for Adaptive Irrigation Scheduling," *IEEE Access*, vol. 11, pp. 33201–33212, 2023.