



“Design and Implementation of an AI-Enabled Autonomous Spraying Robot for Precision Agriculture”

Tanuja Wakchaure¹, Allen Dhanam², Harshdip Patil³, Abhijit Hingmire⁴, Sitaram Longani⁵

¹ Student, ENTC Department, ISBMCOE, Pune, tanujawakchaure50@gmail.com

² Student, ENTC Department, ISBMCOE, Pune, allendhanam@gmail.com

³ Student, ENTC Department, ISBMCOE, Pune, harshdipatil9319@gmail.com

⁴ Student, ENTC Department, ISBMCOE, Pune, abhijithingmire78@gmail.com

⁵ Asst. Professor, ENTC Department, ISBMCOE, Pune, sitaramlongani@gmail.com

ABSTRACT :

The increasing demand for sustainable and efficient farming has driven the integration of artificial intelligence (AI) and robotics in modern agriculture. This paper presents the design and development of an **AI-enabled autonomous spraying robot** capable of performing precision pesticide and fertilizer application in agricultural fields. The system integrates computer vision, AI-based plant recognition, and autonomous navigation to reduce chemical wastage and environmental contamination. The robot employs an embedded microcontroller, machine learning algorithms, and ultrasonic sensors for terrain navigation and target detection. A convolutional neural network (CNN) model classifies crop regions and detects weed or pest-infected zones for selective spraying. The hardware framework consists of a four-wheeled rover equipped with a spray nozzle system, a camera module, and a pump unit controlled via a real-time AI inference engine. Experimental evaluation demonstrates an accuracy of 93.8% in crop classification and a 27% reduction in pesticide consumption compared to conventional spraying methods. This work highlights the potential of AI-driven robotics to enhance productivity, minimize resource utilization, and support sustainable agricultural practices.

Keywords—Artificial Intelligence, Precision Agriculture, Autonomous Robot, Spraying System, Machine Learning, Computer Vision, Convolutional Neural Network.

1. Introduction

The agricultural industry is undergoing technological transformation, with automation and artificial intelligence (AI) emerging as essential tools for improving efficiency and sustainability. One of the major challenges in modern agriculture is the **inefficient use of pesticides and fertilizers**, which not only increases costs but also negatively impacts soil health, biodiversity, and human health. Traditional spraying techniques lack precision, leading to excessive chemical use and uneven distribution.

To address these issues, **autonomous spraying robots** have gained significant attention in recent years. These robots can autonomously navigate through farmlands, identify crop health conditions, and spray chemicals only where necessary. The integration of AI, computer vision, and IoT sensors allows such robots to make intelligent, data-driven decisions in real-time.

The main objective of this research is to design an **AI-enabled autonomous spraying robot** capable of detecting crop types, identifying infected areas, and performing targeted pesticide application. The system aims to:

1. Improve spraying accuracy and efficiency.
2. Minimize chemical wastage.
3. Reduce human exposure to harmful pesticides.
4. Enhance crop yield through precision treatment.

2. Literature Review

Numerous studies have explored automation in agriculture, particularly focusing on **robotic spraying systems** and **AI-based crop analysis**.

In [1], Ryu et al. developed an autonomous agricultural robot equipped with image sensors for row detection. Similarly, [2] introduced a vision-based spraying system capable of recognizing crop leaves using machine learning. A CNN-based weed detection model proposed in [3] achieved high accuracy but lacked autonomous mobility.

AI and deep learning have proven particularly effective in **disease detection**. As shown in [4], convolutional neural networks can classify crop diseases with over 90% accuracy. However, these systems often require large datasets and high computational resources, which can be challenging for low-cost embedded systems.

In [5], a Raspberry Pi-based smart spraying system was proposed, which could detect weed patches and selectively spray chemicals. While this system reduced pesticide usage, it lacked terrain adaptability and full autonomy. Recent advancements in robotics, such as **SLAM (Simultaneous Localization and Mapping)** algorithms [6], allow robots to autonomously navigate in complex environments.

Other studies, such as [7]–[9], integrated IoT-based monitoring with AI for smart farming. However, these implementations often relied on stationary sensors rather than mobile robotic platforms. Our proposed system combines these technologies to achieve **autonomous mobility, intelligent decision-making, and adaptive spraying** using AI-driven perception.

3. System Architecture

The proposed AI-enabled autonomous spraying robot consists of **three major subsystems**:

1. **Perception Layer (Vision and Sensors)**
2. **Control and Processing Layer (AI and Embedded System)**
3. **Actuation Layer (Mobility and Spraying Mechanism)**

3.1 Perception Layer

The perception layer captures real-time data from multiple sensors. A high-resolution camera module mounted on the front captures live video frames, which are processed through a CNN model to identify crops, weeds, and infected regions. Ultrasonic sensors are used for obstacle detection and distance measurement, while GPS provides global positioning for navigation.

3.2 Control and Processing Layer

This layer integrates AI algorithms and embedded control. A Raspberry Pi 4 acts as the main controller, handling AI inference and communication. A secondary microcontroller (Arduino Mega) manages low-level actuation such as motor control and pump activation. The CNN model is trained on an agricultural dataset containing images of healthy and diseased plants. It classifies each frame into one of three categories:

- **Healthy crop area**
- **Weed area**
- **Infected crop area**

3.3 Actuation Layer

The actuation system includes:

- **DC motors** for wheel movement.
- **Servo motor** for nozzle direction adjustment.
- **Water pump** connected to a chemical container.
- **Solenoid valve** for controlling spray flow.

The robot's chassis is built with lightweight aluminum to ensure stability and mobility. The pump activation is triggered based on AI classification results.

4. Methodology

4.1 Dataset Preparation

A custom dataset of **10,000 images** was collected from agricultural fields and open repositories such as PlantVillage. Each image was labeled for crop type and infection category. Data augmentation techniques—rotation, brightness adjustment, and flipping—were applied to increase robustness.

4.2 CNN Model Architecture

The model consists of:

- **Input layer:** 128×128 RGB images
- **Convolutional layers:** Extract spatial features
- **Pooling layers:** Reduce dimensionality
- **Dense layer:** Fully connected classifier
- **Softmax output layer:** Predicts class probabilities

The model was trained using **Adam optimizer**, **learning rate = 0.001**, and **cross-entropy loss** for 50 epochs. The final accuracy achieved was **93.8%** on the validation dataset.

4.3 Navigation Algorithm

The navigation system is based on **PID control** and **sensor fusion**.

- Ultrasonic sensors detect obstacles at multiple angles.
- A line-following algorithm enables the robot to stay aligned with crop rows.
- GPS assists in coverage tracking and field mapping.

4.4 Spraying Mechanism

The robot’s spraying system activates automatically when the AI model identifies infected or weed zones. The spray intensity and duration are dynamically adjusted based on the **severity score** estimated by the CNN output confidence.

4.5 Power Management

The system is powered by a **12V Li-ion battery pack** with a solar charging module for field sustainability. Power regulation ensures consistent operation for up to 4 hours of continuous spraying.

5. Experimental Setup

5.1 Hardware Components

- Raspberry Pi 4 (4GB)
- Arduino Mega 2560
- Ultrasonic Sensors (HC-SR04)
- GPS Module (NEO-6M)
- Motor Driver (L298N)
- DC Motors (300 RPM)
- Servo Motor (SG90)
- Water Pump and Solenoid Valve
- 12V Battery and Solar Charger

5.2 Software Components

- Python 3.9, Open CV, Tensor Flow, NumPy
- Arduino IDE for motor control
- MQTT for communication
- TensorFlow Lite for edge inference

6. Results and Discussion

The system was tested in both **controlled lab conditions** and **outdoor agricultural fields**. Performance metrics included accuracy, precision, and chemical consumption.

Parameter	Conventional Spraying	Proposed System
Spraying Accuracy	70.2%	93.8%
Chemical Usage (L/acre)	4.2	3.1
Crop Damage Risk	High	Low

Parameter	Conventional Spraying	Proposed System
Average Coverage Time (min/acre)	15	11

6.1 AI Model Performance

The CNN achieved:

- Precision: 92.7%
 - Recall: 91.5%
 - F1 Score: 92.1%
- The model demonstrated resilience against lighting variations due to augmentation.

6.2 Navigation Efficiency

The robot successfully avoided obstacles with a **97% success rate**. The average deviation from predefined paths was within **±5 cm**, ensuring reliable field coverage.

6.3 Chemical Savings

By selectively spraying only infected zones, chemical use was reduced by 27%, improving cost efficiency and environmental safety.

6.4 Discussion

The integration of AI and robotics achieved autonomous spraying without manual intervention. However, real-world challenges such as uneven terrain and poor lighting affected accuracy slightly. Future versions can integrate **LiDAR** and **multispectral imaging** for enhanced detection.

7. Applications

- **Precision Pesticide Spraying:** Reduces human exposure and chemical waste.
- **Crop Health Monitoring:** Detects stress or disease early.
- **Weed Detection and Targeted Control:** Minimizes herbicide usage.
- **Data Logging and Cloud Integration:** Enables long-term farm analytics.

8. Conclusion

This paper demonstrates the successful implementation of an **AI-enabled autonomous spraying robot** for precision agriculture. The integration of CNN-based image classification and real-time embedded control provides intelligent and efficient spraying. Experimental results confirm significant improvements in accuracy and resource conservation compared to traditional methods.

Future work will focus on **enhancing autonomy** through LiDAR-based navigation, **edge AI optimization** for faster inference, and **cloud connectivity** for large-scale deployment. The system marks a step forward toward sustainable and data-driven smart farming.

REFERENCES

- [1] S. Ryu et al., "Vision-based autonomous agricultural robot for row crop navigation," *IEEE Access*, vol. 8, pp. 20134–20142, 2020.
- [2] K. Patel and P. Chauhan, "Smart pesticide spraying system using machine vision," *IEEE Trans. Agric. Eng.*, vol. 67, no. 4, pp. 341–347, 2021.
- [3] M. Ahmed et al., "Deep CNN for weed detection in precision agriculture," *Computers and Electronics in Agriculture*, vol. 187, p. 106279, 2021.
- [4] A. Kamilaris and F. Prenafeta-Boldú, "Deep learning in agriculture: A survey," *Computers and Electronics in Agriculture*, vol. 147, pp. 70–90, 2018.
- [5] R. Singh et al., "Low-cost smart spraying robot for crop protection," *Proc. IEEE Int. Conf. on Smart Computing and Communications*, 2021.
- [6] B. Zhao, "Autonomous navigation using SLAM in agricultural environments," *IEEE Robotics and Automation Letters*, vol. 6, no. 3, pp. 4839–4846, 2021.
- [7] Y. Li and Z. Wang, "IoT-based precision agriculture monitoring system," *IEEE Internet of Things Journal*, vol. 8, no. 5, pp. 3413–3424, 2021.
- [8] M. Koirala et al., "Machine learning-based crop disease detection for sustainable farming," *IEEE Access*, vol. 9, pp. 53312–53325, 2021.
- [9] J. Das et al., "Robotics for precision agriculture: Challenges and opportunities," *IEEE Robotics and Automation Magazine*, vol. 28, no. 3, pp. 46–57, 2021.

2021.

- [10] N. Thakur et al., "AI in smart agriculture: A case study on autonomous sprayers," *IEEE Access*, vol. 10, pp. 111209–111220, 2022.
- [11] D. K. Gupta et al., "Autonomous pesticide spraying drone using AI," *IEEE Int. Conf. on Intelligent Systems*, 2020.
- [12] P. R. Sharma et al., "AI-based crop identification for smart farming," *IEEE Sensors Journal*, vol. 22, no. 6, pp. 5842–5851, 2022.
- [13] R. F. Ahmad and H. S. Khan, "Path planning of agricultural robots using AI optimization," *IEEE Transactions on Automation Science and Engineering*, vol. 18, no. 2, pp. 667–678, 2021.
- [14] J. K. Lee, "Autonomous robotic sprayer for greenhouse environments," *IEEE Access*, vol. 9, pp. 22431–22442, 2021.
- [15] M. T. Alam, "Intelligent spraying control system based on plant health analysis," *IEEE Trans. Industrial Informatics*, vol. 19, no. 2, pp. 1459–1470, 2023.
- [16] G. D. Jones, "AI-powered precision agriculture for resource optimization," *IEEE Access*, vol. 9, pp. 180512–180525, 2021.
- [17] P. S. Ghosh, "Comparative study of ML models for disease detection in crops," *IEEE Access*, vol. 9, pp. 146712–146724, 2021.
- [18] K. Nguyen et al., "Energy-efficient navigation of agricultural robots," *IEEE Trans. Automation Science and Engineering*, vol. 18, no. 4, pp. 1154–1164, 2021.
- [19] V. T. Rathore, "Smart IoT-enabled robotic sprayer for sustainable farming," *Proc. IEEE Int. Conf. on Smart Technologies*, 2022.
- [20] L. Zhang, "AI-enhanced agricultural robotics for crop care," *IEEE Transactions on Robotics*, vol. 38, no. 5, pp. 2667–2679, 2022.